



designed for scientists



RCT 5 digital

/// Data Sheet

The new magnetic stirrer RCT 5 digital with 850 W offers significantly more power making it an ideal device for demanding stirring tasks up to 20 l.

Multifunctional menu

Whether determining the direction of rotation, timer functions or sequence programming - the stirring process can be programmed individually from beginning to end. In this way, the reaction runs reliably and safely even without monitoring.



designed for scientists

Scratch-resistant ceramic coating

RCT 5 digital has a rectangular set-up plate with a white, ceramic coating. It is less scratch-prone than conventional magnetic stirrer plates.

Safety features

The display is made of chemical resistant and hardened glass which increases the safety of the user. In addition, a symbol in the display warns in case of a hot surface and therefore protects from burnings. The safety circuit can be adjusted up to 370 °C.



Technical Data

| | |
|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| Number of stirring positions | 1 |
| Stirring quantity max. per stirring position (H ₂ O) [l] | 20 |
| Motor rating output [W] | 9 |
| Direction of rotation | right / left |
| Speed display set-value | LCD |
| Speed display actual-value | LCD |
| Speed control | Turning knob |
| Speed range [rpm] | 50 - 1500 |
| Setting accuracy speed [rpm] | 10 |
| Stirring bar length [mm] | 30 - 80 |
| Self-heating of the set-up plate by max. stirring (RT:22°C/duration:1h) [+K] | 13 |
| Heat output [W] | 850 |
| Temperature display set-value | LCD |
| Temperature display actual-value | LCD |
| Temperature unit | °C / °F |
| Heating temperature range [°C] | Room temp. + device self heating - 310 |
| Heat control | Turning knob |
| Temperature setting range [°C] | 0 - 310 |
| Temperature setting resolution of heating plate [K] | 1 |
| Connection for ext. temperature sensor | PT1000, ETS-D5, ETS-D6 |
| Temperature setting resolution of medium [K] | 1 |
| Adjustable safety circuit [°C] | 50 - 370 |
| Set-up plate material | Aluminum with ceramic coating |
| Set-up plate dimensions [mm] | 137 x 137 |
| Automatic reverse rotation | yes |
| Intermittent mode | yes |
| Viscosity trend measurement | yes |
| Timer | yes |
| Timer display | LCD |
| Time setting min. [s] | 1 |
| Time setting max. [min] | 143940 |
| Sensor in medium detection (Error 5) | yes |
| Speed deviation (no load, nominal voltage, at 1500rpm + 25 °C) [±%] | 2 |
| Heating rate (1l H ₂ O in H1500) [K/min] | 7.5 |
| Heat control accuracy of heating plate (at 100°C) [±K] | 5 |
| Heat control accuracy with ext. PT1000 (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [±K] | 0.5 |
| Heat control accuracy with ETS-D5 (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [±K] | 0.5 |
| Heat control accuracy with ETS-D6 (500ml H ₂ O in 600ml beaker, 40mm stirring bar, 600rpm, 50°C) [±K] | 0.2 |
| Dimensions (W x H x D) [mm] | 160 x 85 x 270 |
| Weight [kg] | 2.6 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative humidity [%] | 80 |
| Protection class according to DIN EN 60529 | IP 42 |
| RS 232 interface | yes |
| USB interface | yes |
| Voltage [V] | 220 - 230 / 115 / 100 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 900 |



designed for scientists

Power input standby [W]

1.6

